

## Neutrik Line I/O to Dante® Interfaces

Neutrik are always creating something new. Please see their latest Line I/O to Dante® Interfaces, available from DWR Distribution.

### NA-2I2O-DLINE



Connect your legacy audio gear to the DANTE® world. The Line I/O to DANTE® Interface is an end-of-network device. It is a breakout box which allows two channels of audio to be integrated into a DANTE® network. Simultaneously, NA-2I2O-DLINE converts a DANTE® stream into analog audio signals. Hence, it is possible to use this tiny box to feed analog audio signals into the DANTE® network while at the same time receiving a mix from another DANTE® source.

Line I/O to DANTE® Interface is designed for harsh stage conditions. It therefore features lockable chassis connectors for both the audio and network connections. For fixed installations, the rubber protection can be removed. With optional

mounting brackets or a rack panel, the box can be mounted below tables, in floor boxes, or in equipment racks.

### NA-2O-DLINE



Connect your legacy audio gear to the DANTE® world. The Line I/O to DANTE® Interface is an end-of-

network device. It is a breakout box which allows two channels of audio to be integrated into a DANTEÂ® network. Simultaneously, NA-2I2O-DLINE converts a DANTEÂ® stream into analog audio signals. Hence, it is possible to use this tiny box to feed analog audio signals into the DANTEÂ® network while at the same time receiving a mix from another DANTEÂ® source.

Line I/O to DANTEÂ® Interface is designed for harsh stage conditions. It therefore features lockable chassis connectors for both the audio and network connections. For fixed installations, the rubber protection can be removed. With optional

mounting brackets or a rack panel, the box can be mounted below tables, in floor boxes, or in equipment racks.

## NA-2I-DLINE



Connect your legacy audio gear to the DANTEÂ® world. The Line I/O to DANTEÂ® Interface is an end-of-network device. It is a breakout box which allows two channels of audio to be integrated into a DANTEÂ® network. Simultaneously, NA-2I2O-DLINE converts a DANTEÂ® stream into analog audio signals. Hence, it is possible to use this tiny box to feed analog audio signals into the DANTEÂ® network while at the same time receiving a mix from another DANTEÂ® source.

Line I/O to DANTEÂ® Interface is designed for harsh stage conditions. It therefore features lockable chassis connectors for both the audio and network connections. For fixed installations, the rubber protection can be removed. With optional

mounting brackets or a rack panel, the box can be mounted below tables, in floor boxes, or in equipment racks.