

MAJOR for JIMS

08 August 2011

DWR Distribution introduced MAJOR to the industry at Mediatech. The fixtures are perfect for exhibitions and may be considered for the Johannesburg International Motor Show coming up in October – ***DWR is currently running a special on these fixtures.***

Source Four PAR EA CDM



re with discharge lamp

The MAJOR Source Four PAR EA CDM is ideal for shops,

object lighting, congress rooms and exhibitions at which a specific light intensity and outstanding colour rendering is required.

The MCM (“Metal Cold Mirror”) version of this spotlight, which radiates approximately 90% of the heat to the rear, also allows use in temperature-sensitive environments, such as art galleries. The various, interchangeable front lenses and colour filter options allow the PAR EA CDM to be universal in terms of areas of application.

- External electronic PSU, fitted to the yoke
- Low heat generation
- Reception for dichroic filters and colour changers
- Energy saving CDM lamp
- Long lamp life cycle of 9,000hrs
- Excellent colour reproduction due to daylight spectrum
- Comprehensive accessories available
- The housing can be supplied in black, white, silver-grey (RAL 9006) or any other RAL colour

Scope of Delivery

External electronic PSU, colour filter frame and four front lenses, mains plug

Technical Information

Operating voltage/ supply voltage: 230V

Lamp power: 35W/70W/150W/250W

Socket: G12

Weight: 3,4kg

Dimensions: 273 x 260 x 279mm

Input connector: Schuko

Gel size: 190 x 190mm

Type of protection (IP): 20

Colour temperature (K): 3.000/4.200°K

Safety bond Saveking®, 3mm, 1m, w/ quick link (5mm), black

For more information, see:

[https://www.lightpower.de/index.php?id=131&L=1&tx_mpcightpowerproductdb_pi2\[showUid\]=80](https://www.lightpower.de/index.php?id=131&L=1&tx_mpcightpowerproductdb_pi2[showUid]=80)

Source Four Daylight PAR

575W HSD

Extremely bright PAR luminaire with discharge lamp



The MAJOR Source Four Daylight PAR is ideal for larger buildings and shopping centres, conference rooms and trade fairs and especially for vehicle presentations where a high light yield and defined beam angle are required.

The various exchangeable front lenses and colour filter options mean this very strong spotlight is a real all-rounder.

- **External electronic PSU**
- **Auto restrike function**
- **Daylight colour temperature 7.200°K**
- **Reception for dichroic filters and colour changers**
- **Wide range of accessory available**

Technical Information

Operating voltage/ supply voltage: 230V

Lamp power: 575W HSD/MSD

Socket: GX9,5

Weight: 5,8kg

Dimensions: 273 x 260 x 279mm

Input connector: Schuko

Gel size: 190 x 190mm

Type of protection (IP): 20

Colour temperature (K): 7.200°K

Safety bond Saveking®, 3mm, 1m, w/ quick link (5mm), black

For more information, please see:

[https://www.lightpower.de/index.php?id=131&L=1&tx_mplightpowerproductdb_pi2\[showUid\]=79](https://www.lightpower.de/index.php?id=131&L=1&tx_mplightpowerproductdb_pi2[showUid]=79)