



Dewey II 63A 3-Phase Distro





EARTH LEAKAGE VERSION



NON - EARTH LEAKAGE VERSION

APPLICATION:

High quality scalable power distribution for the Professional Audio Visual, Rental, Staging and Installation Markets.

KEY FEATURES:

- High Quality Rack Mount Enclosure
- Durable Laser Engraved Legend
- High Quality Circuit Breakers



- Rugged Connectors
- Integrated 3-Phase Digital Multimeter
- Microprocessor Controlled L1-L2-L3-N-E Status LED
- Designed to be used with our range of Socapex Sub-Distribution boards
- · Service power outlets on dedicated Earth
- Leakage (Independent of main system)

OPTIONS:

Earth Leakage
30mA Earth leakage protection
No Earth leakage protection **
4 additional paralleled 19-Pin Socapex Outlets
Remote monitoring option ***
Stainless steel enclosure option for corrosive environments

SPECIFICATIONS:

Inputs

1 x 63A 380V 3-Phase L1-L2-L3+N+E 1 x 5-Pin 63A C-form plug on 1.5m cable 1 x 4-Pole 63A Overload Breaker

Outputs

4 x 19-Pin Socapex Outlets with 24 Independent Circuits

- Each outlet wired to 6-ch Lighting Standard
- 24 x 16A 1-Pole Overload Breaker

Service Outlets

30mA Earth Leakage Protected Service Sub-Distribution Board 3 x 16A SA Service Plug * 3 x 16A 1-Pole Overload Breaker

- * Available with BS Standard / Euro Standard Outlet
- ** Please consult local electrical regulations for approvals
- *** Requires separate network management unit (sold separately)

DIMENSIONS:

19? Rack Standard6u Rack Space436.4mm Mounting depth

Download brochure